

# Cordless Angle Drill DDA450 / DDA451 13 mm (1/2")







Capacity of drill chuck: 2-13mm (1/16" - 1/2")

#### **DDA451**

#### Bit sleeve



7/16" (approx 11mm) Hex shank bit





# **High maneuverability**

Compact and lightweight for increased maneuverability in various work postures and reduced user fatigue









#### **Mechanical 2-speed transmission**



- Able to drill large diameter holes in low speed mode Able to do drilling with 2-9/16" self-feed bit that
- the models of competitor M cannot do

#### **Hook assembly (anti-drop attachment)**



- · Also can be used as a skyhook. • Anti-drop strap can be attached.

## Cordless Angle Drill Line-up











### Cordless Angle Drill DDA450 / DDA451 13 mm (1/2")

#### Capacity Steel: 13 mm (1/2") 🙀 Variable Speed

🖊 Brake Reversing

Mechanical 2-Speed

Soft Start Built-in Job Light

Carrying Case

**Hex Shank** No Load Speed (RPM) Max Fastening Torque Vibration Level Sound Pressure Level

Sound Power Level Dimensions (L x W x H)

Net weight

Wood (Self-Feed Bit) Hi: 50 mm (2") Wood (Self-Feed Bit) Lo: 65 mm (2-9/16") Wood (Hole Saw) Hi: 101 mm (4") Wood (Hole Saw) Lo: 127 mm (5") Wood (Auger-Bit): 38 mm (1-1/2") DDA451: 11.1 mm (7/16")

High / Low: 0 - 1,400 / 0 - 450
High: 26 N·m (230 in.lbs.) / Low: 70 N·m (620 in.lbs.)
Drilling into Metal: 2.5 m/s<sup>2</sup> or less
83 dB(A) 94 dB(A)

DDA450: 434 x 82 x 179 mm (17-1/8 x 3-1/4 x 7") DDA451: 434 x 82 x 163 mm (17-1/8 x 3-1/4 x 6-3/8") DDA450: 3.2 - 3.5 kg (7.1 - 7.7 lbs.) DDA451: 2.8 - 3.3 kg (6.2 - 7.3 lbs.)

Standard Equipment: Chuck Key (DDA450 only), Chuck Key Holder (DDA450 only), Side Grip, Hook (DDA450 only), + Screw(DDA450 only), Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area

## Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan