Satisfy Professional's Needs

LXT

Cordless Driver Drill
DDF491 13 mm (1/2")

4 tools in 1

Maximum versatility for any job.

18V LITHIUM-ION












BL MOTOR XPT

Four quick-change heads

let you drill, drive, and work in tight spaces—without the need for additional tools.

Max fastening torque
65 N·m

Usable even without attachments.
A C-form driver bit is securely held by a built-in magnet.



20-stage torque settings allow for fine adjustments to suit the task at hand.

Mechanical 2-speed

4 tools in 1

Drill chuck attachment set
Part No. 1918F1-0

Keyless drill chuck with metal single-sleeve for basic drilling and screwdriving

Hex bit attachment set
Part No. 1918F2-8 (M type)
Part No. 1918F3-6 (N type)

Compact design for screwdriving in tight spaces
Toolless quick bit replacement with push-in installation and pull-sleeve release

Offset attachment set
Adjustable to 16 different angles every 22.5 degrees when installed on the tool
Part No. 1918F4-4 (M type)
Part No. 1918F5-2 (N type)

Compact design for screwdriving in corners and tight spaces
Toolless quick bit replacement with push-in installation and pull-sleeve release

Angle attachment set
Adjustable to 16 different angles every 22.5 degrees when installed on the tool
Part No. 1918F6-0

Compact design for screwdriving in tight spaces

Accepts connection of the other three attachments



Can also be used without any of the three attachments.



LED job light

Variable speed control by trigger
allows for speed adjustments based on the material or application.

XPT (eXtreme Protection Technology)

Charging Time

	Fast Charging DC18RC	DC18SD
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 min	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 min	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min
18V LITHIUM-ION / LXT BASIC — Compatible with charger DCB18WA only		DCB18WA
BLB182 2.0Ah		90 min

Charge the LXT batteries with the LXT battery chargers and the LXT BASIC battery with the LXT BASIC battery charger.

Cordless Driver Drill

DDF491 13 mm (1/2")

- Variable Speed
- Brake
- Reversing
- Mechanical 2-Speed
- Keyless Chuck
- Torque Setting 20
- Built-in Job Light
- Carrying Case

**EN62841-2-1, Mode: Drilling into metal, Attachment type: Drill chuck attachment*

No load speed	*High: 0 - 1,900 min⁻¹* *Low: 0 - 500 min⁻¹*
Capacity	*Wood (Self-feed bit): 38 mm (1-1/2")* *Steel: 13 mm (1/2")*
Max fastening torque	*Max: 65 N·m (580 in.lbs.)* *Hard: 50 N·m (440 in.lbs.)* *Soft: 27 N·m (240 in.lbs.)*
Chuck capacity	*13 mm (1/2")*
Vibration level	*2.0 m/s² **
Uncertainty (K) for Vibration	*1.5 m/s² **
Sound pressure level	*79 dB(A) (EN62841-2-1)*
Sound power level	*87 dB(A) (EN62841-2-1)*
Uncertainty (K) for Noise	*3 dB(A) (EN62841-2-1)*
Dimensions (L x W x H) (Battery)	*186 x 81 x 255 mm (7-3/8 x 3-3/16 x 10") (BL1850B) W/ Drill chuck attachment*
Net weight (Battery)	*1.8 kg (4.0 lbs.) (BL1850B)*

Standard Equipment : Hook, Phillips bit, Drill chuck attachment, Hex bit attachment, Offset attachment, Angle attachment

Standard equipment and accessories, product appearance and specifications may vary by country or region, and all test results, including work amount per charge and work efficiency, are for reference only and may vary depending on application and operating conditions.

Makita Corporation
3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202607

www.makita.com