



Cordless Impact Driver DTD156

Satisfy Professional's Needs



Max fastening torque **155N·m**



Work amount
on a single full
battery charge















560 pcs.

Drove 90mm coarse thread
screws into melapi.
with BL1850B (5.0Ah)



Max fastening torque: 155N·m



<div></div>			<div></div> <div>DC18RC</div>	<div></div> <div>DC18SD</div>	<div>Cordless Impact Driver</div> <div>DTD156</div> <div>5</div>
<div></div> <div>BL1815N 1.5Ah</div>	<div>15 min</div>	<div>30 min</div>	<div></div> <div>Variable Speed</div>	<div>Capacity</div> <div>Machine Screw: M4 - M8 (5/32" - 5/16")</div> <div>Standard Bolt: M5 - M14 (3/16" - 9/16")</div> <div>High Strength Bolt: M5 - M12 (3/16" - 1/2")</div> <div>Coarse thread (in length): 22 - 125 mm (7/8" - 4-7/8")</div>	
<div></div> <div>BL1820B 2.0Ah</div>	<div>24 min</div>	<div>45 min</div>	<div></div> <div>Brake</div>	<div>Hex Shank</div> <div>6.35 mm (1/4")</div>	
<div></div> <div>BL1830B 3.0Ah</div>	<div>22 min</div>	<div>60 min</div>	<div></div> <div>Reversing</div>	<div>No Load Speed (RPM)</div> <div>0 - 2,500</div>	
<div></div> <div>BL1840B 4.0Ah</div>	<div>36 min</div>	<div>90 min</div>	<div></div> <div>Built-in Job Light</div>	<div>Impacts Per Minute (IPM)</div> <div>0 - 3,000</div>	
<div></div> <div>BL1850B 5.0Ah</div>	<div>45 min</div>	<div>110 min</div>	<div></div> <div>Carrying Case</div>	<div>Max Fastening Torque</div> <div>155 N·m (1,370 in.lbs.)</div>	
<div></div> <div>BL1860B 6.0Ah</div>	<div>55 min</div>	<div>130 min</div>	<div>Standard Equipment:</div> <div>Belt Clip, Battery, Charger</div>	<div>Vibration Level</div> <div>10.0 m/s²</div>	
				<div>Sound Pressure Level</div> <div>92 dB(A)</div>	
				<div>Sound Power Level</div> <div>103 dB(A)</div>	
				<div>Dimensions (L x W x H)</div> <div>w/ BL1815N / BL1820B: 143 x 79 x 223 mm (5-5/8 x 3-1/8 x 8-3/4")</div> <div>w/ BL1830B / BL1840B / BL1850B / BL1860B: 143 x 79 x 241 mm (5-5/8 x 3-1/8 x 9-1/2")</div>	
				<div>Net weight</div> <div>1.3 - 1.6 kg (2.9 - 3.6 lbs.)</div>	

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202104